

XP-58IIK

58mm Thermal Receipt Printer

Fast. Reliable. Versatile.
Built for Every Business.



High Operational Reliability

Supports both front and top paper exit for flexible use in any environment.



Drop-in Paper Loading

Easy paper loading design improves efficiency and reduces downtime.



QR Code & IAP

Support QR code printing and IAP online for easy management.



Multi-Language Support

Supports multiple international languages to meet global business needs.



XP-58IIK
Thermal Receipt Printer

Model	XP-58IIK
Resolution	203 DPI
Printing method	Direct thermal
Paper width	57.5±0.5mm
Print width	48 mm
Column capacity	384 dots/line
Max. print speed	90mm/s
Interface	USB/USB+Serial / USB+Blueooth/ USB+Blueooth+Serial / USB+Blueooth+Serial+WiFi
Line spacing	3.75mm (Adjustable by commands)
Fonts Symbology	
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24
Characters /Line	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D Barcode	QR code
Input buffer	32 Kbytes
NV Flash	64 Kbytes
Power	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A
Power source	DC 12V/2.6A
Cash drawer	DC 12V/1A
Physical characteristics	
Weight	0.498 Kg
Dimensions	121.8×110×114.6 mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
Reliability	
Printer head life	50 KM
Software	
Emulation	ESC/POS
Driver	Windows/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/ Android/ Windows



Print Method
Direct Thermal



Paper Width
58mm



Max. Print Speed
Up to 90mm/s



Resolution
203 DP



Interface
USB

Ideal for Multiple Applications



Retail & Catering



Beauty & Leisure



Transportation & Logistics



Medical & Health



Banking & Government Affairs



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

