




XP-V1 / XP-C1

Thermal Receipt Scanner Printer



Thermal Receipt Scanner Printer

XP-V1 / XP-C1

- Support IAP online upgrade
- Support fixed USB port
- Support print density adjustment
- Support expansion of wired or wireless scanning devices



Model	XP-V1	XP-C1
Resolution	203 DPI	
Printing method	Direct thermal	
Print width	48 mm	
Column capacity	384 dots/line	
Max. print speed	90 mm/s	
Interface	USB+Bluetooth	
Line spacing	3.75mm (Adjustable by commands)	
Media type	Continuous paper	
Media width	58mm	
Media roll diameter	60mm±0.5mm	
Media thickness	0.06~0.08mm	
Fonts Symbology		
Character size	Afont A:12×24, Font B: 9×17, CHN: 24*24	
Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 /ITF / CODABAR / CODE93 / CODE128 / QR code / PDF417	
Code page	PC347(Standard Europe) / Katakana / PC850(Multilingual) /PC860(Portuguese)/ PC863(Canadian-French)/PC865(Nordic)/ West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII / Latvian / Arabic / PT151(1251)	
Memory	96 Kbytes	
Flash	256 M	
Power		
Power adaptor	AC 100V/220V, 50 ~ 60Hz, 1.0A	
Power source	DC 9V / 2A	
Cash drawer	DC 12V / 1A	
Physical characteristics		
Weight	0.57 kg	
Dimensions	160×113×93mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45°C), humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60°C), humidity(10 ~ 90%)	
Reliability		
Auto cutter	/	Partial
Cutter life	/	0.5 million cuts
Printer head life	50 KM	50Km
Software		
Emulation	ESC/POS	
SDK	Windows / Android / iOS	
Driver	Windows/ Linux/ MacOS/ Android	



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 393 2978
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

