

XP-T230L / T300L Thermal Receipt Printer



Model	XP-T230L	XP-T300L
Printing method	Direct thermal	
Paper width	79.5±0.5mm×φ80mm	
Print width	72mm	72mm (adjustable by command)
Column capacity	576 dots/line(adjustable by command)	
Max. print speed	230 mm/s	300 mm/s
Interface	USB+Serial / USB+Lan	USB+Serial+Lan
Line spacing	3.75mm(Adjustable by commands)	
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	

Cutter		
Auto cutter	Partial	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	64 Kbytes	4096 Kbytes
NV Flash	256 Kbytes	256 Kbytes

Power		
Power adaptor	Input: AC 220V, 50 ~ 60Hz	
Power source	Output: DC 24V/2.5A	
Cash drawer output	DC 24V/1A	

Physical characteristics		
Weight	1.78 Kg	
Dimensions	198×148×138mm (D×W×H)	

Environmental Requirements		
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)	


Reliability		
Cutter life	1.5 million cuts	
Printer head life	150Km	

Software		
Emulation	ESC/POS	
Driver	Windows/JPOS/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS, Android, Windows	



XP-T230L / T300L Thermal Receipt Printer

- Water proof, oil proof, dust proof design
- Wifi, Bluetooth option
- Led light and sound alarm
- Wall mountable design



APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing



Express



Factory



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

